

Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Replaced version: 3.0.0, issued: 04.03.2014 Region: GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 **Product identifier**

Trade name

## Boardmarker refill ink 119501, 119901 contained in: TZ 1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Refilling ink

#### 1.3 Details of the supplier of the safety data sheet

LegaMaster GmbH Kwinkweerd 62 Postbus 111

7240 AC Lochem

Netherlands

+31 (0) 573-713000 Telephone no. Information provided by / telephone +31 (0) 573-713000

## **Advice on Safety Data Sheet**

sdb\_info@umco.de

#### 1.4 **Emergency telephone number**

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 2; H225 **STOT SE 3: H336** 

Classification in accordance with Directive 67/548/EEC or 1999/45/EC

F; R11 R67

#### 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

## Hazard pictograms



GHS02



## Signal word

Danger

## Hazardous component(s) to be indicated on label:

1-methoxy-2-propanol

## **Hazard statements**

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.



Trade name: Boardmarker refill ink 119501, 119901 contained in: TZ 1

Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Reglaced version: 3.0.0, issued: 04.03.2014 Region: GB

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 for extinction.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

### 2.3 Other hazards

No data available.

## **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

### **Hazardous ingredients**

No	Substance name		Additional information		
	CAS / EC / Index /	Classification	Classification (EC)	Concentration	%
	REACH no	67/548/EEC	1272/2008 (CLP)		
1	ethanol				
	64-17-5	F; R11	Flam. Liq. 2; H225	> 50.00 - < 100.00	%-b.w.
	200-578-6				
	603-002-00-5				
	-				
2	1-methoxy-2-propa	nol			
	107-98-2	R10	Flam. Liq. 3; H226	> 10.00 - < 25.00	%-b.w.
	203-539-1	R67	STOT SÉ 3; H336		
	603-064-00-3				
	-				

Full Text for all R-phrases, H-phrases and EUH-phrases: pls. see section 16

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

### **General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

## After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

### After skin contact

Wash off immediately with soap and water.

### After eye contact

Remove contact lens. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

### After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.



Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Reglaced version: 3.0.0, issued: 04.03.2014 Region: GB

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

### Suitable extinguishing media

Sand; Extinguishing powder; Carbon dioxide; Water spray jet

### Unsuitable extinguishing media

High power water jet

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO); Nitrogen oxides (NOx)

## 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

## 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

### 6.4 Reference to other sections

No data available.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

### Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

## Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

## 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

## Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

### Advice on storage assembly

None known



Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Reglaced version: 3.0.0, issued: 04.03.2014 Region: GB

## 7.3 Specific end use(s)

No data available.

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

## Occupational exposure limit values

No	Substance name	CAS no.		EC no.			
1	ethanol	64-17-5		200-578-6			
	List of approved workplace exposure limits (WELs) / B	List of approved workplace exposure limits (WELs) / EH40					
	Ethanol						
	TWA	1920	mg/m³	1000	ml/m³		
2	1-methoxy-2-propanol	107-98-2		203-539-1			
	2000/39/EWG						
	1-Methoxypropanol-2						
	STEL	568	mg/m³	150	ml/m³		
	TWA	375	mg/m³	100	ml/m³		
	Skin resorption / sensibilisation	Skin					
	List of approved workplace exposure limits (WELs) / EH40						
	1-Methoxypropan-2-ol						
	STEL	560	mg/m³	150	ml/m³		
	TWA	375	mg/m³	100	ml/m³		
	Skin resorption / sensibilisation	Sk					

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

## Personal protective equipment

## **Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

## Eye / face protection

Safety glasses with side protection shield (EN 166)

### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

### Other

Normal chemical work clothing.

## **Environmental exposure controls**

No data available.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Form/Colour	
liquid	
black	

Odour	
characteristic	



Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Replaced version: 3.0.0, issued: 04.03.2014 Region: GB

Odour threshold			
No data available			
pH value			
not determined			
Boiling point / boiling range No data available			
Melting point / melting range No data available			
Decomposition point / decomposition range No data available			
Flash point Value		13	°C
Ignition temperature Value		287	°C
Auto-ignition temperature Remarks	Product is not selfi	gniting.	
Oxidising properties No data available			
Explosive properties  This product is not explosive. In and after use da	nger of production of	of inflamn	nable compounds.
Flammability (solid, gas) No data available			
Lower flammability or explosive limits Value		1.7	% vol
Upper flammability or explosive limits			
Value		15.0	% vol
Vapour pressure			
Value Reference temperature		59 20	hPa °C
Vapour density			
No data available			
Evaporation rate  No data available			
Relative density			
No data available			
Density No data available			
Solubility in water Remarks	partially miscible		
Solubility(ies) No data available			
Partition coefficient: n-octanol/water No data available			
Viscosity No data available			
Solvent content			
Value		79.4	%



Trade name: Boardmarker refill ink 119501, 119901 contained in: TZ 1

Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Replaced version: 3.0.0, issued: 04.03.2014 Region: GB

## 9.2 Other information

Other information
No data available.

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No data available.

### 10.2 Chemical stability

No data available.

## 10.3 Possibility of hazardous reactions

No data available.

## 10.4 Conditions to avoid

None known

## 10.5 Incompatible materials

None known.

## 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

Acute oral toxicity					
No	Substance name	CAS no.		EC no.	
1	1-methoxy-2-propanol	107-98-2		203-539-1	
LD50			5660	mg/kg bodyweight	
Species		rat			
Source		Manufacturer			

Acute dermal toxicity						
No	Substance name	CAS no.		EC no.		
1	1-methoxy-2-propanol	107-98-2		203-539-1		
LD5	0		9999.99	mg/kg bodyweight		
Spec	cies	rabbit				
Soul	rce	Manufacturer				



Trade name: Boardmarker refill ink 119501, 119901 contained in: TZ 1

Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Reglaced version: 3.0.0, issued: 04.03.2014 Region: GB

### Acute inhalational toxicity

No data available

### Skin corrosion/irritation

No data available

## Serious eye damage/irritation

No data available

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

### Reproduction toxicity

No data available

### Carcinogenicity

No data available

## STOT-single exposure

No data available

### STOT-repeated exposure

No data available

### Aspiration hazard

No data available

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.



Trade name: Boardmarker refill ink 119501, 119901 contained in: TZ 1

Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Region: 3.0.0, issued: 04.03.2014 Region: GB

## **SECTION 12: Ecological information**

### 12.1 Toxicity

## Toxicity to fish (acute)

No data available

### Toxicity to fish (chronic)

No data available

### Toxicity to Daphnia (acute)

No data available

## **Toxicity to Daphnia (chronic)**

No data available

### Toxicity to algae (acute)

No data available

## Toxicity to algae (chronic)

No data available

### **Bacteria toxicity**

No data available

## 12.2 Persistence and degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Other adverse effects

No data available.

## 12.7 Other information

## Other information

Do not discharge product unmonitored into the environment.

### **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

### **Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

### **Packaging**

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.



Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Reglaced version: 3.0.0, issued: 04.03.2014 Region: GB

## **SECTION 14: Transport information**

## 14.1 Transport ADR/RID/ADN

Class Classification code F1 Packing group Ш Hazard identification no. 33 **UN** number UN1263 Technical name **PAINT** Special Provision 640 640D D/E Tunnel restriction code Label 3

## 14.2 Transport IMDG

 Class
 3

 Packing group
 II

 UN number
 UN1263

 Proper shipping name
 PAINT

 EmS
 F-E+S-E

 Label
 3

## 14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263
Proper shipping name Paint
Label 3

### 14.4 Other information

No data available.

## 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Remarks

Annex I, part 2, category 7 b

## 15.2 Chemical safety assessment

No data available.

## **SECTION 16: Other information**

## Sources of key data used to compile the data sheet:

EC Directive 67/548/EC resp. 1999/45/EC as amended in each case.

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.



Trade name: Boardmarker refill ink 119501, 119901 contained in: TZ 1

Product no.: TZ1 schwarz

Current version: 4.0.0, issued: 10.09.2014 Region: 3.0.0, issued: 04.03.2014 Region: GB

## Full text of the R-, H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these

sections)

R10 Flammable. R11 Highly flammable.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

## Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183, D-21107 Hamburg

Tel.: +49 40 / 79 02 36 300 Fax: +49 40 / 79 02 36 357 e-mail: umco@umco.de

This information is based on our present state of knowledge and experience.

The security data sheet describes products with a view to the security requirements.

However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

## Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.